

SPEC SHEET

LED Lumaflood Light

- Aluminum Rust Proof Body
- Instant Start Electric Unit
- Suitable for Wet Location
- Branded Chip



STDC10FLOOD
STDC30FLOOD
STDC50FLOOD

Description

Our Lumafloods can be mounted at almost any angle with the provided U bracket. They feature an aluminum, rust proof body and are rated IP65 for indoor or outdoor use. It is designed to deliver high efficiency and reduced wattages, our Lumaflood flood lights create bright, shadow-free security and spot or up-lighting for a variety of outdoor applications, including facades, landscapes, public places, retail and residential complexes, and hospitality. Available in 10 Watt, 30 Watt, or 50 Watt.

Specifics

Wattage:	10 Watt, 30 Watt, or 50 Watt
Voltage:	120v
Color Temp.:	Cool White 5k or Warm White 3k
Brightness:	750, 2300, or 3500 Lumens
Beam Angle:	140°
Lifespan:	± 30,000 - 50,000 hours
Environment:	Suitable for Indoor or Outdoor Use
Finish:	Bronze

SKU	Wattage	Brightness	Size	Color Temperature
STDC10FLOOD	10W	750 Lumens	4-1/2" L x 3-3/8" W x 3-1/2" H	Cool White 5k or Warm White 3k
STDC30FLOOD	30W	2300 Lumens	9" L x 7-1/4" W x 5" H	Cool White 5K
STDC50FLOOD	50W	3500 Lumens	11-1/4" L x 9-1/4" W x 5-5/8" H	Cool White 5k or Warm White 3k

